




RECYCLED SHINY POLYAMIDE

N232 SIRIUS REC

N232 SIRIUS REC

COMPOSITION (ASTM STANDARD ±3% TOLERANCE)		WEIGHT (±5% TOLERANCE)		WIDTH (+3% / -2% TOLERANCE)		COURSES		WALES			
80% TRILOBAL RECYCLED SHINY POLYAMIDE	20% ELASTANE HIGH-CHLORINE RESISTANCE	175 G/M ²		150 CM		44 / CM		25 / CM			
		5.2 OZ/YD ²		59 INCHES		112 / INCHES		64 / INCHES			
DIMENSIONAL CHANGE OF FABRIC AFTER HL AATCC 135-2015 (1 WASH, NORMAL CYCLE AT 41 DEGREE CELSIUS LINE DRY)		RESISTANCE TO PILLING ASTM D 3512-RANDOM TUMBLE AT 30 MINUTES PHOTOGRAPHIC RATING STD		ULTRAVIOLET PROTECTION FACTOR (U.P.F.) AATCC 183-2010							
MAX -5% WIDTH	MAX -5% LENGTH	4.0 TO 4.5		40 TO 50+							
STRETCH TO DYNAMOMETER (±15%) ASTM D4964 - LOAD 20 LBS		SOLID			PFP						
		110% WIDTH (MIN 94% - MAX 127%)		175% LENGTH (MIN 149% - MAX 201%)		110% WIDTH (MIN 94% - MAX 127%)		165% LENGTH (MIN 140% - MAX 201%)			
MODULUS @ % ELONGATION (30% - 50% - 70%)		30%	50%	70%	30%	50%	70%	30%	50%	70%	
		0.2 - 0.8	0.8 - 1.4	1.4 - 3.2	0.0 - 0.3	0.4 - 1.1	1.1 - 1.9	0.3 - 0.9	1.0 - 1.8	2.1 - 3.9	
CARE LABELLING SYMBOLS		    									



2518 CHAMPAGNE

9917 DARK OLIVE

2319 BLACK

1410 WHITE / 1910 PFP

AATCC STANDARDS

COLOUR	CHLORINATED WATER AATCC 162	LIGHT AATCC 16-20 AFU	WATER 38°C AATCC 107						SEA WATER 38°C AATCC 106						PERSPIRATION AATCC 15						CROCKING AATCC 8		WASHING 49°C AATCC 61-2A								
	C.C.	C.C.	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	S.CO DRY	S.CO WET	C.C.	AC	CO	PA	PL	PC
1410 / 1910	3	3	4.5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5		
9917	4	4	4.5	4	4	3.5	4	4	4	4.5	4	4	4	4.5	4.5	4	4.5	4.5	4.5	4.5	4.5	4.5	3.5	4.5	4.5	4.5	3.5	4.5	4		
2518	4	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5			
2319	4.5	4.5	4.5	4	4.5	3.5	4.5	4.5	3.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4	4.5	4.5	4.5	4.5	4	4	3	4.5	4.5	4.5	3.5	4.5	4.5	

ISO STANDARDS

COLOUR	CHLORINATED WATER ISO 105-E03	LIGHT ISO 105-B02	WATER ISO 105-E01						SEA WATER ISO 105-E02						ALKALINE PERSPIRATION PH 8.0 ISO 105-E04						CROCKING ISO 105-X12		WASHING 40°C ISO 105-C06 A25								
	C.C.	C.C.	C.C.	CO	PA	PL	C.C.	CO	PA	PL	C.C.	CO	PA	PL	C.C.	CO	PA	PL	S.CO DRY	S.CO WET	C.C.	CO	PA	PL	PL	S.CO DRY	S.CO WET	C.C.	CO	PA	PL
1410 / 1910	2-3	3	4-5	5	5	5	4-5	5	5	5	4-5	5	5	5	4-5	5	5	5	5	5	4-5	5	5	5	5	5	5	5	5	5	
9917	3-4	4	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	3-4	4-5	4-5	4	4-5	4-5	4-5	4-5	4-5	4-5
2518	3	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5	4-5
2319	4	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4	4	3	4-5	4-5	4-5	4	4-5	4-5	4-5

ALL COLORS DISPLAYED IN THE MAIN SHINY COLOR CARD ARE AVAILABLE FOR SAMPLING ON THIS ITEM. PLEASE REFER TO THE MAIN SHINY COLOR CARD FOR THE COLOR FASTNESS PERFORMANCES OF EACH COLOR. YOU CAN PLACE BULK ORDERS WITH MCQ 70 MTS IN ANY SHADE OF OUR COLLECTION. HOWEVER, THE RESULTING COLOR SHADE AND THE COLOR FASTNESS PERFORMANCES MAY BE SLIGHTLY DIFFERENT. WE WILL SUBMIT TO YOUR ATTENTION A LAB DIP SWATCH FOR APPROVAL BEFORE GOING ON WITH THE BULK PRODUCTION.

SPECIAL NOTES/WARNINGS WE RECOMMEND CARRYING OUT LAB TESTS FOR COLOR MATCHES, MOLDING, BONDING AND APPLICATIONS ON FABRICS IN ORDER TO PREVENT PROBLEMS FROM ARISING DURING GARMENTS PRODUCTION. PLEASE CAREFULLY CHECK PHYSICAL DATA AND COLOR FASTNESS FORECASTS.

