

N610 JUSTIN



9019 nero



0614 amaranta



1010 white - 1210 white PFP



5316 new blu cina

N610 JUSTIN

Applications

> Swimwear > Beachwear > Underwear

Elegant and stylish, Justin fits the body like a second skin. Designed for easy-fit underwear items, it is pleasant to wear, lightweight, breathable and comfortable.



9019 black



0614 amaranta



1010 white - 1210 white PFP



5316 new blu cina

Composition

Polyamide		Elastane	
77%		23%	
Weight (±5%)		Width (+3%/-2%)	
155 g/m²	231 g/m lin.	147 cm	
Courses	Wales	Tolerance for composition (standard ASTM)	
46/cm	25/cm	±3%	
Dimensional Change of fabric after HL AATCC 135-2015 (1 wash, normal cycle at 41 degree Celsius line dry)		Max	Max
		-5%	-5%
		Width	Length
Resistance to pilling ASTM D 3512-Random tumble at 30 minutes photographic rating STD		4 to 4.5	
Ultraviolet Protection Factor (U.P.F.) AATCC 183-2010		40/50+	
Stretch to dynamometer (±15%) ASTM D 4964 - LOAD 20 LBS		210%	135%
		Width	Length
		(min 179% - max 242%)	(min 115% - max 155%)
Modulus % elongation (30% - 50% - 70%)		30%	50%
		0.0 - 0.2	0.2 - 0.7
		0.7 - 1.2	0.2 - 0.8
		0.8 - 1.4	1.4 - 2.4
		Width Lbs	Length Lbs
Care labelling codes			

AATCC Standards

COLOUR	CHLORINATED WATER AATCC 162	LIGHT AATCC 16-20 AFU	WATER 38°C AATCC 107							SEA WATER 38°C AATCC 106							PERSPIRATION AATCC 15							CROCKING AATCC 8		WASHING 49°C AATCC 61-2A						
	C.C.	C.C.	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	S.CO DRY	S.CO WET	C.C.	AC	CO	PA	PL	PC	WO
	1010	3	3	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	5	5	4.5	5	5	5	5	5
1210	3	3	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	5	5	4.5	5	5	5	5	5	5
0614	4	4.5	4.5	4.5	4.5	4	4.5	4.5	4.5	4.5	4.5	4	4	4.5	4.5	4	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	3	4.5	4.5	4.5	3.5	4	4.5	4.5
5316	2.5	3.5	4.5	3.5	3	2.5	3	3	2.5	4.5	4	3	2.5	3	3	2.5	4.5	4.5	4	3.5	4.5	4.5	3.5	4.5	3.5	4	4.5	3.5	3	4.5	4.5	3.5
9019	4.5	4.5	4.5	4	4	3.5	4	4	4	4.5	4	4	3.5	4	4	4	4.5	4.5	4.5	4	4.5	4.5	4.5	4.5	3.5	4.5	4.5	4	3.5	4	4.5	4

ISO Standards

COLOUR	CHLORINATED WATER ISO 105-E03	LIGHT ISO 105-B02	WATER ISO 105-E01			SEA WATER ISO 105-E02			ALKALINE PERSPIRATION PH 8.0 ISO 105-E04			ACID PERSPIRATION PH 5.5 ISO 105-E04			CROCKING ISO 105-X12		WASHING 40°C ISO 105-C06 A2S		
	C.C.	C.C.	C.C.	CO	PA	C.C.	CO	PA	C.C.	CO	PA	C.C.	CO	PA	S.CO DRY	S.CO WET	C.C.	CO	PA
	1010	2-3	3	4-5	5	5	4-5	5	5	4-5	5	5	4-5	5	5	5	5	4-5	5
1210	2-3	3	4-5	5	5	4-5	5	5	4-5	5	5	4-5	5	5	5	5	4-5	5	5
0614	3-4	4-5	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	3	4-5	4-5	4
5316	2	3	4-5	4	3	4-5	4	3-4	4-5	3-4	3	4-5	4	3	4-5	3-4	4-5	3-4	3-4
9019	4-5	4-5	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	3-4	4-5	4-5	3-4

Available colors: the 4 colors presented in this page are always available for sampling. If you would like to choose a color from the main Polyamide color card, you can enjoy a MCQ of only 70 mts for bulk orders. However, the resulting color shade and the color fastness performance may be slightly different. We will submit to your attention a lab dip swatch for approval before going on with the bulk production.

Special notes/warnings: we recommend carrying out lab tests for color matches, molding, bonding and applications on fabrics in order to prevent problems from arising during garments production. Please carefully check physical data and color fastness forecasts.



N610 JUSTIN



soft touch



extra comfort



two way stretch



UV protection



high chlorine resistance