

N880 HAWAII

EVERYDAY VERSATILITY

APPLICATIONS & TECHNICAL DATA

WORK TO PLAY
JOGGERS

SOFT TENNIS
OUTFITS

FITNESS & RUNNING
SHORTS



PROVISIONAL

COMPOSITION

(ASTM STANDARD ±3% TOLERANCE)

76%

RECYCLED
NYLON

24%

ELASTANE
HIGH-CHLORINE RESISTANCE

WEIGHT

(±5% TOLERANCE)

WIDTH

(+3% / -2% TOLERANCE)

165 G/M²

145 CM

4.86 OZ/YD²

57 INCHES

COURSES

52 / CM

WALES

29 / CM

132 / INCHES

74 / INCHES

DIMENSIONAL CHANGE OF FABRIC AFTER HL
AATCC 135-2015 (1 WASH, NORMAL CYCLE AT 41
DEGREE CELSIUS LINE DRY)

MAX -4%
WIDTH

MAX -4%
LENGHT

RESISTANCE TO PILLING
ASTM D 3512-RANDOM TUMBLE AT 30 MINUTES
PHOTOGRAPHIC RATING STD

4.0 TO 4.5

ULTRAVIOLET PROTECTION FACTOR (U.P.F.)
AATCC 183-2010

50+

SOLID FABRIC

STRETCH TO DYNAMOMETER (±15%)
ASTM D4964 - LOAD 20 LBS

155%

WIDTH
(MIN 132% - MAX 178%)

110%

LENGTH
(MIN 94% - MAX 127%)

MODULUS @ % ELONGATION (30% - 50% - 70%)

30%	50%	70%	30%	50%	70%
0.2 - 0.6	0.6 - 1.2	1.2 - 2.0	0.5 - 1.2	1.5 - 2.5	2.6 - 4.6

CARE LABELLING SYMBOLS




6816 GLOBE



4718 COCOA POWDER



0919 NERO



0210 WHITE SOLID / 0120 WHITE PFP