


N112 KIRA REC

COMPOSITION (ASTM STANDARD ±3% TOLERANCE)		WEIGHT (±5% TOLERANCE)			WIDTH (+3% / -2% TOLERANCE)			COURSES			WALES		
80% RECYCLED POLYAMIDE	20% ELASTANE HIGH-CHLORINE RESISTANCE	190 G/M ²			150 CM			49 / CM			26 / CM		
		5.6 OZ/YD ²			59 INCHES			124 / INCHES			66 / INCHES		
DIMENSIONAL CHANGE OF FABRIC AFTER HL AATCC 135-2015 (1 WASH, NORMAL CYCLE AT 41 DEGREE CELSIUS LINE DRY)		RESISTANCE TO PILLING ASTM D 3512-RANDOM TUMBLE AT 30 MINUTES PHOTOGRAPHIC RATING STD						ULTRAVIOLET PROTECTION FACTOR (U.P.F.) AATCC 183-2010					
MAX -5% WIDTH	MAX -5% LENGHT	4.0 TO 4.5						50+					
STRETCH TO DYNAMOMETER (±15%) ASTM D4964 - LOAD 20 LBS		SOLID						PFP					
		115% WIDTH (MIN 98% - MAX 132%)			210% LENGTH (MIN 179% - MAX 242%)			105% WIDTH (MIN 89% - MAX 121%)			195% LENGTH (MIN 165% - MAX 224%)		
MODULUS @ % ELONGATION (30% - 50% - 70%)		30%	50%	70%	30%	50%	70%	30%	50%	70%	30%	50%	70%
		0.2 - 0.9	0.9 - 1.8	1.8 - 3.6	0.0 - 0.2	0.3 - 1.0	1.0 - 1.6	0.4 - 0.8	1.0 - 2.0	2.3 - 4.3	0.0 - 0.2	0.4 - 1.0	0.8 - 1.8
CARE LABELLING SYMBOLS													



● 5316 NEW BLU CINA



0614 AMARANTA



0919 NERO



0210 WHITE / 0120 PFP

AATCC STANDARDS

COLOUR	CHLORINATED WATER AATCC 162	LIGHT AATCC 16-20 AFU	WATER 38°C AATCC 107								SEA WATER 38°C AATCC 106								PERSPIRATION AATCC 15								CROCKING AATCC 8		WASHING 49°C AATCC 61-2A							
	C.C.	C.C.	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	S.CO DRY	S.CO WET	C.C.	AC	CO	PA	PL	PC	WO				
0210 / 0120	3	3	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5	5	5	4.5	5	5	5	5	5	5				
0614	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	3.5	4.5	4.5	4.5	3.5	4.5	4.5	4.5				
5316 ●	3.5	3.5	4.5	4.5	4.5	3.5	4.5	4.5	4	4.5	4.5	4.5	3.5	4.5	4.5	3.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	3.5	4	4.5	4	3.5	4.5	4.5	3.5				
0919	4.5	4.5	4.5	4.5	4	4	4.5	4.5	4	4.5	4.5	4	4	4.5	4.5	4	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	3.5	4.5	4.5	4	4	4.5	4.5	4				

ISO STANDARDS

COLOUR	CHLORINATED WATER ISO 105-E03	LIGHT ISO 105-B02	WATER ISO 105-E01				SEA WATER ISO 105-E02				ALKALINE PERSPIRATION PH 8.0 ISO 105-E04				ACID PERSPIRATION PH 5.5 ISO 105-E04				CROCKING ISO 105-X12		WASHING 40°C ISO 105-C06 A2S			
	C.C.	C.C.	C.C.	CO	PA	PL	C.C.	CO	PA	PL	C.C.	CO	PA	PL	C.C.	CO	PA	PL	S.CO DRY	S.CO WET	C.C.	CO	PA	PL
	50 MG/L																							
0210 / 0120	2-3	3	4-5	5	5	5	4-5	5	5	5	4-5	5	5	5	4-5	5	5	5	5	5	4-5	5	5	5
0614	3-4	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	3	4-5	4-5	4	4-5
5316 ●	2-3	3	4-5	4-5	4	4-5	4-5	4-5	3-4	4-5	4-5	4	3-4	4	4-5	4-5	3-4	4	4-5	3-4	4-5	3-4	3-4	4
0919	4-5	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	3	4-5	4-5	3-4	4

ALL COLORS DISPLAYED IN THE MAIN POLYAMIDE COLOR CARD ARE AVAILABLE FOR SAMPLING ON THIS ITEM. PLEASE REFER TO THE MAIN POLYAMIDE COLOR CARD FOR THE COLOR FASTNESS PERFORMANCES OF EACH COLOR. YOU CAN PLACE BULK ORDERS WITH MCQ 70 MTS IN ANY SHADE OF OUR COLLECTION. HOWEVER, THE RESULTING COLOR SHADE AND THE COLOR FASTNESS PERFORMANCES MAY BE SLIGHTLY DIFFERENT. WE WILL SUBMIT TO YOUR ATTENTION A LAB DIP SWATCH FOR APPROVAL BEFORE GOING ON WITH THE BULK PRODUCTION.

SPECIAL NOTES/WARNINGS WE RECOMMEND CARRYING OUT LAB TESTS FOR COLOR MATCHES, MOLDING, BONDING AND APPLICATIONS ON FABRICS IN ORDER TO PREVENT PROBLEMS FROM ARISING DURING GARMENTS PRODUCTION. PLEASE CAREFULLY CHECK PHYSICAL DATA AND COLOR FASTNESS FORECASTS.

SWIMWEAR

THE GREEN TURN OF OUR EVERGREEN N110 KIRA. ONE OF THE MOST WANTED ARTICLES OF OUR RECYCLED COLLECTION. BUILT ON THE SAME RELIABLE FEATURES OF THE ORIGINAL VIRGIN VERSION, KIRA REC HAS OPENED A NEW CHAPTER OF THE STORY OF HUNG YEN SUSTAINABLE FABRICS COLLECTION.



HIGH CHLORINE
RESISTANCE



UV
PROTECTION



FOUR WAY
STRETCH



COMFORT
FIT



DIGITAL
PRINTING



CONSCIOUSLY
MANUFACTURED



CU1004128

CREORA
Highclo