

N320 MAMI SOLID + PFP



TECHNICAL DATASHEET 12/05/2025

COMPOSITION (ASTM STANDARD ±3% TOLERANCE)			WEIGHT (±5% TOLERANCE)			WIDTH (+3% / -2% TOLERANCE)			COURSES			WALES			
77% NYLON	23% ELASTANE HIGH-CHLORINE RESISTANCE	215 g/m²	150 cm			46 / cm			26 / cm						
		6.3 oz/yd²	59 inches			117 / inch			66 / inch						
DIMENSIONAL CHANGE OF FABRIC AFTER HL AATCC 135 (1 wash, normal cycle at 41-degree Celsius, tumble dry low)				max -5% WIDTH						max -5% LENGTH					
RESISTANCE TO PILLING ASTM D 3512-RANDOM TUMBLE AT 30 MINUTES PHOTOGRAPHIC RATING STD				4.5											
ULTRAVIOLET PROTECTION FACTOR (U.P.F.) AATCC 183				50+											
STRETCH TO DYNAMOMETER (±15%) ASTM D4964 - LOAD 20 Lbs MODULUS @ % ELONGATION (30%- 50%- 70%)				SOLID						PFP					
				100% WIDTH (min 85% - max 115%)			170% LENGTH (min 145% - max 196%)			95% WIDTH (min 81% - max 110%)			170% LENGTH (min 145% - max 196%)		
				30%	50%	70%	30%	50%	70%	30%	50%	70%	30%	50%	70%
				0.4-0.9	0.9-2.0	2.0-4.0	0.2-0.8	0.8-1.6	1.6-2.6	0.6-1.2	1.6-2.8	3.4-6.6	0.0-0.6	0.8-1.5	1.5-2.5
CARE LABELLING CODES															

CERTIFICATIONS



UPF 50+

FUNCTIONAL YARNS



SPECIAL RECOMMENDATIONS: WE RECOMMEND TESTING EACH DYE BATCH BEFORE ANY TREATMENT OR APPLICATION OTHER THAN CUTTING AND SEWING.

To improve our product's quality, we reserve the right to modify these data while necessary.