

# N850 FISHTALE PRINTED

TECHNICAL DATASHEET August 2026



| COMPOSITION<br>(ASTM STANDARD ±3% TOLERANCE)                                                                   |                                                            | WEIGHT<br>(±5% TOLERANCE) | WIDTH<br>(+3%/-2% TOLERANCE)          | COURSES   | WALES                                   |            |         |         |
|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|---------------------------|---------------------------------------|-----------|-----------------------------------------|------------|---------|---------|
| 80%<br>RECYCLED<br>NYLON                                                                                       | 20%<br>RECYCLED<br>ELASTANE<br>HIGH-CHLORINE<br>RESISTANCE | 200 g/m²                  | 143 cm                                | 51/ cm    | 28/ cm                                  |            |         |         |
|                                                                                                                |                                                            | 5.9 oz/yd²                | 56.3 inches                           | 130/ inch | 71/ inch                                |            |         |         |
|                                                                                                                |                                                            |                           |                                       |           |                                         |            |         |         |
| DIMENSIONAL CHANGE OF FABRIC AFTER HL<br>AATCC 135 (1 wash, normal cycle at 41-degree Celsius, tumble dry low) |                                                            |                           | max -5%<br>WIDTH                      |           | max -5%<br>LENGTH                       |            |         |         |
|                                                                                                                |                                                            |                           | 4.5                                   |           |                                         |            |         |         |
| RESISTANCE TO PILLING<br>ASTM D 3512-RANDOM TUMBLE AT 30 MINUTES PHOTOGRAPHIC RATING STD                       |                                                            |                           | 50+                                   |           |                                         |            |         |         |
| ULTRAVIOLET PROTECTION FACTOR (U.P.F.)<br>AATCC 183                                                            |                                                            |                           | 50+                                   |           |                                         |            |         |         |
| PRINTED                                                                                                        |                                                            |                           |                                       |           |                                         |            |         |         |
| STRETCH TO DYNAMOMETER (±15%)<br>ASTM D4964 - LOAD 20 Lbs<br><br>MODULUS @ % ELONGATION (30%-50%-70%)          |                                                            |                           | 105%<br>WIDTH<br>(min 89% - max 121%) |           | 170%<br>LENGTH<br>(min 145% - max 196%) |            |         |         |
|                                                                                                                |                                                            |                           | 30%                                   | 50%       | 70%                                     | 30%        | 50%     | 70%     |
|                                                                                                                |                                                            |                           | 0.3-0.8                               | 0.8-1.7   | 2.5-4.8                                 | 0.2-0.6    | 0.7-1.3 | 1.3-2.1 |
|                                                                                                                |                                                            |                           | WIDTH Lbs                             |           |                                         | LENGTH Lbs |         |         |
|                                                                                                                |                                                            |                           | CARE LABELLING CODES                  |           |                                         |            |         |         |
| <div></div> <div></div> <div></div> <div></div> <div></div>                                                    |                                                            |                           |                                       |           |                                         |            |         |         |

## CERTIFICATIONS



UPF 50+

## FUNCTIONAL YARNS



**SPECIAL RECOMMENDATIONS:** WE RECOMMEND TESTING EACH DYE BATCH BEFORE ANY TREATMENT OR APPLICATION OTHER THAN CUTTING AND SEWING.

To improve our product’s quality, we reserve the right to modify these data while necessary.

**Update:** corrected the width in inches; removed highclo logo.

**Replaces the previous data sheet of March 2025.**