



RECYCLED POLYESTER

# P570 LOTUS

COMPOSITION (ASTM STANDARD ±3% TOLERANCE)		WEIGHT (±5% TOLERANCE)	WIDTH (+3% / -2% TOLERANCE)	COURSES		WALES		
85% RECYCLED POLYESTER	15% ELASTANE HIGH-CHLORINE RESISTANCE	130 G/M <sup>2</sup>	150 CM	45 / CM		27 / CM		
		3.8 OZ/YD <sup>2</sup>	59 INCHES	114 / INCHES		69 / INCHES		
DIMENSIONAL CHANGE OF FABRIC AFTER HL AATCC 135-2015 (1 WASH, NORMAL CYCLE AT 41 DEGREE CELSIUS LINE DRY)		RESISTANCE TO PILLING ASTM D 3512-RANDOM TUMBLE AT 30 MINUTES PHOTOGRAPHIC RATING STD			ULTRAVIOLET PROTECTION FACTOR (U.P.F.) AATCC 183-2010			
MAX -5% WIDTH	MAX -5% LENGTH	4.5		30 TO 50+				
STRETCH TO DYNAMOMETER (±15%) ASTM D4964 - LOAD 20 LBS		SOLID						
MODULUS @ % ELONGATION (30% - 50% - 70%)		145% WIDTH (MIN 123% - MAX 167%)	185% LENGTH (MIN 157% - MAX 213%)					
30% 0.1 - 0.3		50% 0.3 - 0.7	70% 0.7 - 1.4	30% 0.0 - 0.1	50% 0.3 - 0.5	70% 0.5 - 1.2		
CARE LABELLING SYMBOLS								



\*2413 NEON PINK

10717 DEEP TEAL

2819 BLACK

4210 WHITE / PFP

## AATCC STANDARDS

COLOUR	CHLORINATED WATER AATCC 162	LIGHT AATCC 16-20 AFU		WATER 38°C AATCC 107				SEA WATER 38°C AATCC 106				PERSPIRATION AATCC 15				CROCKING AATCC 8				WASHING 49°C AATCC 61-2A										
	C.C.	C.C.	C.C.	AC	CO	PA	PL	C.C.	AC	CO	PA	PL	PC	WO	C.C.	AC	CO	PA	PL	PC	WO	S.CO	S.CO	C.C.	AC	CO	PA	PL	PC	WO
																						DRY	WET							
4210	3.5	3.5	4.5	5	5	5	5	5	4.5	5	5	5	5	5	4.5	5	5	5	5	5	5	4.5	5	5	5	5	5	5		
*2413	4	4-10AFU	4.5	4	4.5	4	4.5	4	4.5	4	4.5	4	4.5	4	4.5	4.5	4.5	4.5	4.5	4.5	4	4	4.5	3.5	4	3	4	4.5	4	
10717	4	3.5	4.5	4	4.5	3	4	4	4.5	4	4.5	3.5	4	4	4	4.5	4.5	4.5	4	4.5	4.5	4.5	4.5	4.5	4.5	4	4.5	4		
2819	4.5	4.5	4.5	3.5	4	3	4	4	3.5	4.5	3.5	4	3	4	4.5	3.5	4.5	4	4.5	4.5	4.5	4	4.5	4	4	3	4	4.5	4	

## ISO STANDARDS

COLOUR	CHLORINATED WATER ISO 105-E03	LIGHT ISO 105-B02		WATER ISO 105-E01				SEA WATER ISO 105-E02				ALKALINE PERSPIRATION PH 8.0 ISO 105-E04				ACID PERSPIRATION PH 5.5 ISO 105-E04				CROCKING ISO 105-X12				WASHING 40°C ISO 105-C06 A2S			
	C.C.	C.C.	C.C.	CO	PA	PL	C.C.	CO	PA	PL	C.C.	CO	PA	PL	C.C.	CO	PA	PL	S.CO	S.CO	C.C.	CO	PA	PL	PC	WO	
																			DRY	WET							
4210	3	3-4	4-5	5	5	5	4-5	5	5	5	4-5	5	5	5	4-5	5	5	5	5	5	4-5	5	5	5	5	5	
*2413	3	3	4-5	4-5	4	4-5	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4	4	4-5	4-5	4	4-5	4	4-5	
10717	3-4	3-4	4-5	4-5	3-4	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4-5	4	4-5	4	4-5	4-5	3-4	4	4-5	4-5	3-4
2819	4-5	4-5	4-5	4-5	3-4	4-5	4-5	4-5	3-4	4-5	4-5	4-5	3-4	4-5	4-5	4-5	4-5	3-4	4	4	4-5	4-5	3-4	4	4-5	4-5	3-4

AVAILABLE COLORS THE 4 COLORS PRESENTED IN THIS PAGE ARE ALWAYS AVAILABLE FOR SAMPLING. IF YOU WOULD LIKE TO CHOOSE A COLOR FROM THE MAIN POLYESTER COLOR CARD, YOU CAN ENJOY A MCQ OF 70 MTS FOR BULK ORDERS. HOWEVER, THE RESULTING COLOR SHADE AND THE COLOR FASTNESS PERFORMANCES MAY BE SLIGHTLY DIFFERENT. WE WILL SUBMIT TO YOUR ATTENTION A LAB DIP SWATCH FOR APPROVAL BEFORE GOING ON WITH THE BULK PRODUCTION.

SPECIAL NOTES/WARNINGS WE RECOMMEND CARRYING OUT LAB TESTS FOR COLOR MATCHES, MOLDING, BONDING AND APPLICATIONS ON FABRICS IN ORDER TO PREVENT PROBLEMS FROM ARISING DURING GARMENTS PRODUCTION. PLEASE CAREFULLY CHECK PHYSICAL DATA AND COLOR FASTNESS FORECASTS.

P570 LOTUS

